



Scan Here For More Info



FC 58 - Face Shield

STANDARD : Meets ANSI Z87.1, EN 166

COMPONENT	MATERIAL	ADVANTAGE
Visor	Poly chloride	Covers the entire facial region

COMPONENT	COLOUR	SIZE	THICKNESS	IMPACT RESISTANCE
Visor	Clear	(8 X 15 1/2) inch (203 mm X 394 mm)	1 mm	B (120 m/s)

FEATURES
Poly chloride, transparent mask that extend fully to cover a wearer's face
Edges fitted with aluminium beading for easy adjustment to face contour
Protective films on both sides (Prevent damages and scratches during transportation)
Protects against 99.9% UV protection
Provides wide vision
Protection against high-speed impact
Protects against splashes
Fits over the spec
Best optical quality (Highest ranking at the tests of spherical refractive power, astigmatic refractive power, prismatic refractive power, and light diffusion)
Suitable for different work environment

SERVICES	IDEAL APPLICATIONS
Pharmaceutical	Chemical handling
Chemical	Labs
Cement	Chipping
Construction	Paint shop
Automotive	Material handling

SPECIAL FEATURES



APPLICATION
Protects face exposed to splashes, high speed flying small & medium fragments
Also protects face against irritating mist and potentially infectious materials

STORAGE
Can be stored in the dark for up to 1 year
Do not store direct / high heat or sunlight as this may distort
Can be stored and transported in their original cartons at ambient temperature (0° C to 30°C)

CLEANING	PACKING
Clean cloth can be used	125 pcs per cartoon

Udyogi Plastics Private Limited