



Scan Here For More Info



UD 81 - Safety Spectacle

STANDARD :  IS 5983, ANSI Z87.1, EN 166, CE

INDUSTRY
Construction & projects
Cement
Automotive
Power & utilities
Metals & minings

IDEAL APPLICATIONS
Material handling
Dusty area
Assembly line
Packaging
Medical applications

SPECIAL FEATURES

			
LIGHT WEIGHT	99.9% UV PROTECTION	HARD COATING	LOW IMPACT RESISTANT

COMPONENT	MATERIAL	ADVANTAGE
Lens	Polycarbonate	10 base curve, wrap around design w/side protection
Nose piece	Polycarbonate	Universal, integral to lens
Temple	Polycarbonate	Spatula with soft tip end
Tip	PVC	Slip on the temple
Hinge	Polycarbonate	3 barrel type
Screw	Stainless steel	Standard hinge screw

LENS OPTIONS	OPTICAL CLASS	FILTER	IMPACT RESISTANCE	COATING	WEIGHT
Smoke	1	5-2.5	F (45m/s)	K	20 g.

FEATURES	APPLICATION
Polycarbonate temple with polycarbonate lens	Protects eyes exposed to low-level impacts
Snug-fitting wrap around lens provides perfect impact protection around the eyes	Best used for protection against flying small fragments
Hard coating on lens	
Lens filters out 99.9% of harmful UV light	
On-piece lens, with dual 10 base curvature	
Lens offers users the clearest and the most panoramic view without obstruction	
Modern temple design & soft temple tips contours to fit head shapes without stress	
Incredibly light, resilient & durable protective eyewear for all day wear	
Fashionable design resembles spectacle, suitable for both men and women	
Suitable for different work environment	
STORAGE	
	Can be stored in the dark for up to 2years
	Do not store in direct / high heat or sunlight as this may distort the colour
	Can be stored and transported in their original cartons at ambient temperature (0° C to +30° C)
CLEANING	PACKING
Clean it with the soft cloth	100 pieces per carton

Udyogi